

INNCOM MODEVA THERMOSTAT

The Honeywell INNCOM MODEVA series of thermostats features a capacitive touch interface that's highly configurable and easily customized for your application. These sleek "screwless" touchpoints are easy to clean, and mount securely via magnets rather than screws for a modern look. We can work with you directly to design a unique interface in any color (RAL / Pantone), and can even create a brand standard for your guestroom controls.

MODEVA Thermostats are available in US and British gang box sizes and may be customized to match MODEVA switches. The thermostats can also include Privacy and Service buttons for greater guest convenience.

MODEVA thermostats feature printed circuit-board assemblies (PCBAs) that contain all the necessary components (including logic operations, communications, and user-interface functionality) to operate as a low-voltage controls interface within a thin assembly (8mm), which rests outside of the wall box cavity. The MODEVA thermostat is coupled with an X47 universal relay pack for HVAC control. It communicates by wired S5bus and requires no load assemblies. A PC502 can be added for wireless HVAC control.



Left: MODEVA British Gang Size
Thermostat with Icons and Privacy /
Make-Up-Room Buttons
Right: MODEVA US Vertical Gang
Size Thermostat



Advanced energy
management

Screwless magnetic
mounting system



Wired S5bus
Communication

Optional DND/MUR



Customer
programmable

Fully customizable
programmable
capacitive touch
user interface



May be integrated with
the INNCOM Room
Automation System
over the Deep Mesh
network with INNcontrol
EMS software



Illuminated
Background
LEDs and LCD

MODEVA THERMOSTATS

OPTIONS

Icons may be used instead of text. Ask your sales representative for a representation of standard icons.

Standard MODEVA colors are white and black. If you would prefer custom colors, your Sales Representative will work with your designer to tailor the product to any color from the **Coated Pantone or RAL color guides**. (This will include a design charge and some additional lead time.)

Specifications	
DIMENSIONS	British Single Gang: 86 mm x 86 mm x 10.8 mm (3.4 in x 3.4 in x .4 in) American Single Gang: 119 mm x 74 mm x 8 mm (4.7 in x 2.9 in x .3 in)
POWER SUPPLY	12VDC (+/- 2V)
MOUNTING	Screwless magnetic mounting system into gang box
DISPLAY RESOLUTION	Whole degree F, 0.5 degree C (0.1 degree F in test mode)
PROTOCOL	802.15.4
C/F DEGREES DISPLAY	Toggle Button on front of display
AMBIENT OPERATING*	41 to 149 degrees F (5 to 65 degrees C), 0-95% RH noncondensing
AMBIENT STORAGE	33 to 149 degrees F (1 to 65 degrees C)
FREQUENCY CHANNELS	11-26
APPROVALS	FCC Part 15 compliant

*For indoor use only

For more information
www.inncom.com

Honeywell Hospitality
12 Clintonville Road
Northford, CT 06472
1-800-543-1999

IN-DT-ModevaThermostat | 01-00221 | 2021-07-23
© 2021 Honeywell International Inc.

Honeywell