


Electrical Ratings

Type	Voltage	Resistance Load	Lamp Load	Motor Load
AC (Standard)	AC 125 V AC 250 V	5A 2.5A	44A 22A	5A 2.5A
DC	DC 115 V DC 230 V	0.3A 0.15A		

Flow Rate in Liters per Minute(LPM)

Pipe Size	1"	1-1/4"	1-1/2"	2"	4"	6"	8"	10"	12"	14"	16"	18"	20"
Flow Qty	15	26	29	34.5	74.90	149.90	1013.47	1791.0	2776.0	3729.00	4869.0	5360.00	6687.00
Flow Qty	1PCS	1PCS	1PCS	1 OR 2 PCS	2PCS	3PCS	5PCS	5PCS	5PCS	5PCS	5PCS	5PCS	5PCS


Flow rates averages which may vary ± from pipe. *Equipped with extended paddle trimmed to pipe size




*NOTE


- Individual SUS Paddle are quickly adaptable for 1 inch to 3 inch (25 to 80mm) pipe.
- Standard model is 1 inch to 3 inch

Pressure Loss Rate




Flow-Velocity





Typical Installation



For more information,
<https://honeywellbuildings.in>
 Call: 1-800-103-0339
 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings
 Unitech Trade Center, 5th Floor, Sector-43,
 Block C, Sushant Lok Phase - I,
 Gurgaon - 122 002